

AMBIANCE

HIGH PERFORMANCE WOVENS

Wallcoverings • Panels • Exhibits • Partitions

Inspired by a woven classic, this fashionable fiber mix dresses up any vertical surface with its combination of refined warp yarns offset by subtly variegated boucle filling yarns.

SPECIFICATIONS

WIDTH:	54"	BACKING:	Acrylic
TOTAL WEIGHT:	15 oz. per linear yard	INSTALLATION:	Non-Reversible / Random Match
FINISH:	Stain Repellent	CONTENT:	100% Polyester

PERFORMANCE

FLAMMABILITY:	Passes ASTM E-84 Class A Tested in Accordance with CAN/ULC-S102 Tested in Accordance with (EN13501): B-s1,d0 rating
COLORFASTNESS TO LIGHT:	(AATCC Method 16): Class 4 (40 hours)
ABRASION RESISTANCE:	(ASTM D4157) Exceeds 30,000 Wyzenbeek Double Rubs

QUALITY STANDARDS

ENVIRONMENTAL:	Created with No PVC, No Heavy Metals or Formaldehyde, No ODSs, No Phthalates, No VOCs
CLEANING CODE:	WS & BC – Water/Solvent & Bleach Cleanable

INSTALLATION

Color & texture may vary slightly due to the nature of the fiber & structure.
Installation and maintenance instructions are enclosed with every shipment and should be carefully read prior to installation.
For best results, it is recommended that a qualified textile wallcovering installer be employed.

WARRANTY

5-year limited warranty against manufacturing defects.

USAGE AREAS

HEALTH CARE

- Retirement Facilities
- Nursing Homes
- Hospitals
- Nursing Stations

HOSPITALITY

- Ball Rooms
- Conference Rooms
- Meeting Rooms

DESIGNERS

- Commercial Interiors Market

ENTERTAINMENT

- Theatres
- Recreational Centers

CORPORATE

- Executive Conference Rooms
- General Offices

INSTITUTIONAL

- Schools (Auditorium)
- Government & Mass Trans. Buildings
- Day Care Center