

ARGENT

HIGH PERFORMANCE WOVENS

Wallcoverings • Panels • Exhibits • Partitions

Futuristic high-shen filaments threaded with classic woven yarns create a timeless woven with modern perspective.

SPECIFICATIONS

WIDTH:	55"	INSTALLATION:	Non-Reversible / Random Match
TOTAL WEIGHT:	13.14 oz. per linear yard	CONTENT:	54% Polyolefin, 32% Polyester,
BACKING:	Acrylic		9% Post-Industrial Recycled Polyester,
FINISH:	Stain Repellent		5% Post-Consumer Recycled Polyester

PERFORMANCE

FLAMMABILITY:	Passes ASTM E-84 Class A Tested in Accordance with CAN/ULC-S102 Tested in Accordance with (EN13501): B-s1,d0 rating
COLORFASTNESS TO LIGHT:	(AATCC Method 16): Class 4 (40 hours)
COLORFASTNESS TO CROCKING:	(AATCC Method 8): Class 3 (Wet), Class 4 (Dry)
TEAR STRENGTH: (ASTM D2261-96):	11 (Fill), 22 (Warp)
BREAK STRENGTH: (ASTM 5304-095):	256 (Fill), 246 (Warp)
ABRASION RESISTANCE:	(ASTM D4157) Exceeds 102,000 Wyzenbeek Double Rubs

QUALITY STANDARDS

ENVIRONMENTAL:	Created with No PVC, No Heavy Metals or Formaldehyde, No ODSs, No Phthalates, No VOCs
SUSTAINABLE MATERIALS:	Produced Using Recycled Content
CLEANING CODE:	WS & BC – Water/Solvent & Bleach Cleanable
LEED CONTRIBUTION:	Can Contribute Towards LEED Points

INSALLATION

Color & texture may vary slightly due to the nature of the fiber & structure.
Installation and maintenance instructions are enclosed with every shipment and should be carefully read prior to installation.
For best results, it is recommended that a qualified textile wallcovering installer be employed.

WARRANTY

5-year limited warranty against manufacturing defects.

USAGE AREAS

HEALTH CARE

- Retirement Facilities
- Nursing Homes
- Hospitals
- Nursing Stations

HOSPITALITY

- Ball Rooms
- Conference Rooms
- Meeting Rooms

DESIGNERS

- Commercial Interiors Market

ENTERTAINMENT

- Theatres
- Recreational Centers

CORPORATE

- Executive Conference Rooms
- General Offices

INSTITUTIONAL

- Schools (Auditorium)
- Government & Mass Trans. Buildings
- Day Care Center