

HIGH PERFORMANCE WOVENS

Wallcoverings • Panels • Exhibits • Partitions

Crisp, sleek, and clean all describe this tightly woven dobby fabric with its broad color pallet and sparkling warp accents.

SPECIFICATIONS

WIDTH: **BACKING:** Acrylic Latex

Non-Reversible / Random Match **TOTAL WEIGHT:** 13 oz. per linear yard **INSTALLATION:**

FINISH: StainGuard CONTENT: 100% Polyester

PERFORMANCE

FLAMMABILITY: Passes ASTM E-84 Class A

Tested in Accordance with CAN/ULC-S102

Tested in Accordance with (EN13501): B-s1,d0 rating

COLORFASTNESS TO LIGHT: (AATCC Method 16): Class 4 (40 hours)

(ASTM D4157) Exceeds 30,000 Wyzenbeek Double Rubs **ABRASION RESISTANCE:**

QUALITY STANDARDS

Created with No PVC, No Heavy Metals or Formaldehyde, **ENVIRONMENTAL:**

No ODSs, No Phthalates, No VOCs

CLEANING CODE: WS & BC - Water/Solvent & Bleach Cleanable

INSTALLATION

Customs available upon request. Color & Texture May Vary Slightly Due to the Reflective Quality of the Yarn. Installation and maintenance instructions are enclosed with every shipment and should be carefully read prior to installation. For best results, it is recommended that a qualified textile wallcovering installer be employed.

WARRANTY

5-year limited warranty against manufacturing defects.

USAGE AREAS

HEALTH CARE

• Retirement Facilities

• Nursing Homes

• Hospitals

• Nursing Stations

HOSPITALITY

• Ball Rooms

• Conference Rooms

• Meeting Rooms

DESIGNERS

· Commercial Interiors Market

ENTERTAINMENT

• Theatres

• Recreational Centers

CORPORATE

• Executive Conference Rooms

· General Offices

INSTITUTIONAL

• Schools (Auditorium)

• Government & Mass Trans. Buildings

· Day Care Center



