

CHEVRONEL

HIGH PERFORMANCE WOVENS

Wallcoverings • Panels • Exhibits • Partitions

Tailored bespoke suiting provides quiet elegance and durability when styled as a performance textile that seamlessly blends woven yarns into a classic herringbone weave.

SPECIFICATIONS

WIDTH:	54"	INSTALLATION:	Non-Reversible / Random Match
TOTAL WEIGHT:	12.8 oz. per linear yard	CONTENT:	58% Post-Consumer Recycled Polyester, 42% Polyester
BACKING:	Acrylic		
FINISH:	Stain Repellent		

PERFORMANCE

FLAMMABILITY:	Passes ASTM E-84 Class A Tested in Accordance with CAN/ULC-S102 Tested in Accordance with (EN13501): B-s1,d0 rating
COLORFASTNESS TO LIGHT:	(AATCC Method 16): Class 4 (40 hours)
COLORFASTNESS TO CROCKING:	(AATCC Method 8): Class 4 (Wet), Class 5 (Dry)
TEAR STRENGTH: (ASTM D2261-96):	25+ (Fill), 25+ (Warp)
BREAK STRENGTH: (ASTM 5304-095):	50+ (Fill), 50+ (Warp)
ABRASION RESISTANCE:	(ASTM D4157) Exceeds 50,000 Wyzenbeek Double Rubs

QUALITY STANDARDS

ENVIRONMENTAL:	Created with No PVC, No Heavy Metals or Formaldehyde, No ODSs, No Phthalates, No VOCs
SUSTAINABLE MATERIALS:	Produced Using Recycled Content
CLEANING CODE:	WS & BC – Water/Solvent & Bleach Cleanable
LEED CONTRIBUTION:	Can Contribute Towards LEED Points

INSTALLATION

Color & texture may vary slightly due to the nature of the fiber & structure.
Installation and maintenance instructions are enclosed with every shipment and should be carefully read prior to installation.
For best results, it is recommended that a qualified textile wallcovering installer be employed.
Customs available upon request.

WARRANTY

5-year limited warranty against manufacturing defects.

USAGE AREAS

HEALTH CARE

- Retirement Facilities
- Nursing Homes
- Hospitals
- Nursing Stations

HOSPITALITY

- Ball Rooms
- Conference Rooms
- Meeting Rooms

DESIGNERS

- Commercial Interiors Market

ENTERTAINMENT

- Theatres
- Recreational Centers

CORPORATE

- Executive Conference Rooms
- General Offices

INSTITUTIONAL

- Schools (Auditorium)
- Government & Mass Trans. Buildings
- Day Care Center