

SQUARES

ACOUSTICAL PEEL + STICK TILES

Wallcoverings • Panels • Exhibits • Partitions

Create a custom look with repositionable Peel + Stick Tiles.

SPECIFICATIONS

TILE WIDTH:	13"	BACKING:	Peel + Stick Adhesive
TILE HEIGHT:	13"	INSTALLATION:	Random Match
THICKNESS:	Approximately 3.5mm	CONTENT:	Recycled Polyester
		PACKAGING:	4 Tiles per Box

PERFORMANCE

FLAMMABILITY:	Passes ASTM E-84 Class A
COLORFASTNESS TO LIGHT:	(AATCC Method 16): Class 5 (40 hours)
COLORFASTNESS TO CROCKING:	(AATCC Method 8): Class 4.5 (Wet), Class 4.5 (Dry)
ABRASION RESISTANCE:	Full Commercial Serviceability
ACOUSTICAL NRC (ASTM C-423):	0.15 over gypsum board (*NRC values may vary based on number of units applied. Bulk packaging available.)

QUALITY STANDARDS

FIBER:	Does not absorb moisture. Solution dyed.
ENVIRONMENTAL:	Created with No PVC, No Heavy Metals or Formaldehyde, No ODSs, No Phthalates, No VOCs 45 Plastic Bottles = 1 Box of Tiles
SUSTAINABLE MATERIALS:	Produced Using Recycled Content
CLEANING CODE:	WS & BC – Water/Solvent & Bleach Cleanable
INDOOR AIR QUALITY:	Low V.O.C. Emitting Wallcoverings Meets California Department of Health Services Section 01350 Requirements for Office and School Interior
LEED CONTRIBUTION:	Can Contribute Towards LEED Points

INSTALLATION

Installation and maintenance instructions are enclosed with every shipment and should be carefully read prior to installation. For best results, it is recommended that a qualified textile wallcovering installer be employed.

WARRANTY

5-year limited warranty against manufacturing defects.

USAGE AREAS

HEALTH CARE

- Retirement Facilities
- Nursing Homes
- Hospitals
- Nursing Stations

HOSPITALITY

- Ball Rooms
- Conference Rooms
- Meeting Rooms

DESIGNERS

- Commercial Interiors Market

ENTERTAINMENT

- Theatres
- Recreational Centers

CORPORATE

- Executive Conference Rooms
- General Offices

INSTITUTIONAL

- Schools (Auditorium)
- Government & Mass Trans. Buildings
- Day Care Center

