

SURREY

HIGH PERFORMANCE WOVENS

Wallcoverings • Panels • Exhibits • Partitions

Classic menswear suiting gives a sartorial elegance to the weave of this classic suiting textile pattern.

SPECIFICATIONS

WIDTH:	54"	BACKING:	Acrylic
TOTAL WEIGHT:	17 oz. per linear yard	INSTALLATION:	Non-Reversible / Random Match
FINISH:	Stain Repellent	CONTENT:	49% Polyester, 51% Olefin

PERFORMANCE

FLAMMABILITY:	Passes ASTM E-84 Class A Tested in Accordance with CAN/ULC-S102 Tested in Accordance with (EN13501): B-s1,d0 rating
COLORFASTNESS TO LIGHT:	(AATCC Method 16): Class 4 (40 hours)
COLORFASTNESS TO CROCKING:	(AATCC Method 8): Class 3 (Wet), Class 4 (Dry)
TEAR STRENGTH: (ASTM D2261-96):	20 (Fill), 27 (Warp)
BREAK STRENGTH: (ASTM 5304-095):	228 (Fill), 190 (Warp)
ABRASION RESISTANCE:	(ASTM D4157) Exceeds 63,000 Wyzenbeek Double Rubs

QUALITY STANDARDS

ENVIRONMENTAL:	Created with No PVC, No Heavy Metals or Formaldehyde, No ODSs, No Phthalates, No VOCs
CLEANING CODE:	W & BC – Water & Bleach Cleanable

INSTALLATION

Color & texture may vary slightly due to the nature of the fiber & structure.
Installation and maintenance instructions are enclosed with every shipment and should be carefully read prior to installation.
For best results, it is recommended that a qualified textile wallcovering installer be employed.

WARRANTY

5-year limited warranty against manufacturing defects.

USAGE AREAS

HEALTH CARE

- Retirement Facilities
- Nursing Homes
- Hospitals
- Nursing Stations

HOSPITALITY

- Ball Rooms
- Conference Rooms
- Meeting Rooms

DESIGNERS

- Commercial Interiors Market

ENTERTAINMENT

- Theatres
- Recreational Centers

CORPORATE

- Executive Conference Rooms
- General Offices

INSTITUTIONAL

- Schools (Auditorium)
- Government & Mass Trans. Buildings
- Day Care Center