TRIANGLES

ACOUSTICAL PEEL + STICK TILES

Wallcoverings • Panels • Exhibits • Partitions

Create a custom look with repositionable Peel + Stick Tiles.

SPECIFICATIONS

TILE WIDTH: 13"
TILE HEIGHT: 13"

THICKNESS: Approximately 3.5mm

BACKING: Peel + Stick Adhesive

INSTALLATION:

Random Match

CONTENT: Recycled Polyester

PACKAGING: 8 Tiles per Box

PERFORMANCE

FLAMMABILITY: Passes ASTM E-84 Class A

COLORFASTNESS TO LIGHT: (AATCC Method 16): Class 5 (40 hours)

COLORFASTNESS TO CROCKING: (AATCC Method 8): Class 4.5 (Wet), Class 4.5 (Dry)

ABRASION RESISTANCE: Full Commercial Serviceability
ACOUSTICAL NRC (ASTM C-423): 0.15 over gypsum board

(*NRC values may vary based on number of units applied. Bulk packaging available.)

QUALITY STANDARDS

FIBER: Does not absorb moisture. Solution dyed.

ENVIRONMENTAL: Created with No PVC, No Heavy Metals or Formaldehyde,

No ODSs, No Phthalates, No VOCs 45 Plastic Bottles = 1 Box of Tiles

SUSTAINABLE MATERIALS: Produced Using Recycled Content

CLEANING CODE: WS & BC - Water/Solvent & Bleach Cleanable

INDOOR AIR QUALITY: Low V.O.C. Emitting Wallcoverings Meets California Department of Health Services

Section 01350 Requirements for Office and School Interior

LEED CONTRIBUTION: Can Contribute Towards LEED Points

INSTALLATION

Installation and maintenance instructions are enclosed with every shipment and should be carefully read prior to installation. For best results, it is recommended that a qualified textile wallcovering installer be employed.

WARRANTY

5-year limited warranty against manufacturing defects.

USAGE AREAS

HEALTH CARE

Retirement Facilities

Nursing HomesHospitals

Nursing Stations

HOSPITALITY

• Ball Rooms

• Conference Rooms

Meeting Rooms

DESIGNERS

• Commercial Interiors Market

ENTERTAINMENT

• Theatres

• Recreational Centers

CORPORATE

• Executive Conference Rooms

• General Offices

INSTITUTIONAL

Schools (Auditorium)

• Government & Mass Trans. Buildings

• Day Care Center

